



# CMP35/PAR30LN/FL



|                      |                                                                          |
|----------------------|--------------------------------------------------------------------------|
| <b>Description</b>   | 35W PAR30 Long Neck Flood E26 Base 3000K 80+ CRI<br>Ceramic Metal Halide |
| <b>Ordering Code</b> | 06776                                                                    |
| <b>UNSPSC Code</b>   | 39101614                                                                 |

## Specifications

|                                   |                                                                      |
|-----------------------------------|----------------------------------------------------------------------|
| <b>Watts</b>                      | 35                                                                   |
| <b>Base Type</b>                  | Medium Screw (E26)                                                   |
| <b>Bulb Type</b>                  | PAR 30LN                                                             |
| <b>MOL in/mm</b>                  | 4.92/125                                                             |
| <b>Approx Initial Lumens</b>      | 2400                                                                 |
| <b>Approx Mean Lumens</b>         | 1990                                                                 |
| <b>Approx Initial Max Beam CP</b> | 7500                                                                 |
| <b>CT deg K</b>                   | 3000                                                                 |
| <b>CRI</b>                        | 85+                                                                  |
| <b>Beam Angle</b>                 | 30                                                                   |
| <b>Rated Life</b>                 | 10,000                                                               |
| <b>ANSI Ballast</b>               | M130/O                                                               |
| <b>Fixt Rqmt</b>                  | Open                                                                 |
| <b>Burning Position</b>           | Universal                                                            |
| <b>Special Desc</b>               | Magnetic Ballasts Not Recommended. See instruction's wiring diagram. |

[watch](#) > [like](#) > [follow](#)



selection. solutions. simplicity. [eiko.com](http://eiko.com)

23220 W. 84<sup>th</sup> St, Shawnee, KS 66227 • (P) 1.800.852.2217 (F) 1.800.492.8975  
Canada: 81 King St, Barrie, ON L4N 6B5 • (P) 1.888.410.8151 (F) 1.888.705.1335