



Dependable Power for Any Application

hubbell-acmeelectric.com

www.hubbell.com

240 X 480 - 24/48  
240 X 480 Primary Volts - 24/48 Secondary Volts - 1Ø  
Buck-Boost Transformer - Single Phase

1084



Catalog #: T137921

#### PRODUCT FEATURES

UL listed, CSA certified  
UL Type 3R epoxy encapsulated  
Single or Three Phase Applications  
Wall Mounted  
Covered under Acme's 10 year limited warranty

#### BENEFITS

Easily configured for numerous applications  
Lower cost solution  
5-10 times increase in kVA

#### UL STANDARD

UL 506

#### CSA STANDARD

C22.2 No 47

#### WARRANTY

Acme Electric Warranty Card  
[www.hubbell-acmeelectric.com/Images/news/Acme\\_Warranty.pdf](http://www.hubbell-acmeelectric.com/Images/news/Acme_Warranty.pdf)

#### GENERAL PRODUCT INFORMATION

VA:	-
kVA:	1.50
Primary Voltage:	240 X 480
Secondary Voltage:	24/48
Frequency:	60 Hz
Max Temperature Rise:	115°C
UL Insulation Class:	180°C

#### PRODUCT MEASUREMENTS

Height (In./cm):	11.62 (29.5)
Width (In./cm):	5.50 (14.0)
Depth (In./cm):	5.13 (13.0)

#### CONFIGURATION

Construction Type:	Encapsulated
Mounting Type:	Wall

#### PACKAGING

Ship Weight (Lbs/Kg):	30 (13.6)
-----------------------	-----------

**COMPLIANCES**

UL Standard: UL 506  
UL Listed: File E79947  
CSA Standard: C22.2 No 47  
CSA Listed: LR7357-32  
Warranty: Acme Electric Warranty Card  
[www.hubbell-acmeElectric.com/Images/news/Acme\\_Warranty.pdf](http://www.hubbell-acmeElectric.com/Images/news/Acme_Warranty.pdf)