



Dependable Power for Any Application

[hubbell-acmeelectric.com](http://hubbell-acmeelectric.com)

[www.hubbell.com](http://www.hubbell.com)

120 - 12  
120 Primary Volts - 12 Secondary Volts - 1Ø  
Low Voltage Lighting Transformer - Single Phase

1078



Catalog #: T179621S

#### PRODUCT FEATURES

- UL listed, CSA certified
- UL Type 2 Enclosures
- Fully encapsulated core and coil
- Wall Mounted
- Black Finish UL Type 2 Enclosure
- Input Auto-Thermal reset switch
- Output circuit breaker
- Covered under Acme's 10 year limited warranty

#### BENEFITS

- Copper lead wires for hardwiring
- Primary and secondary overload protection
- Full fault current carrying Farady Shield
- Single and dual knockouts

#### UL STANDARD

UL 506

#### CSA STANDARD

C22.2 No 47

#### WARRANTY

Acme Electric Warranty Card  
[www.hubbell-acmeelectric.com/Images/news/Acme\\_Warranty.pdf](http://www.hubbell-acmeelectric.com/Images/news/Acme_Warranty.pdf)

#### GENERAL PRODUCT INFORMATION

VA:	300
Primary Voltage:	120
Secondary Voltage:	12
Frequency:	60 Hz
Max Temperature Rise:	115°C
UL Insulation Class:	180°C

#### PRODUCT MEASUREMENTS

Height (In./cm):	11.68 (29.7)
Width (In./cm):	4.66 (11.8)
Depth (In./cm):	4.57 (11.6)

#### CONFIGURATION

Construction Type:	Encapsulated
Mounting Type:	Wall
Knockouts (In./Cm):	Two 0.875 (2.2) signal knockouts on each side
Knockouts 2 (In./Cm):	Two dual 0.875 (2.2) and 1.125 (2.9) knockouts on bottom cover

Wiring Diagram: V  
CB Rating: 40 Amp  
CB Style: Push To Reset Thermal Breaker

**PACKAGING**

Ship Weight (Lbs/Kg): 11 (5.0)

**COMPLIANCES**

UL Standard: UL 506  
UL Listed: File E79947  
CSA Standard: C22.2 No 47  
CSA Listed: LR7357-32  
Warranty: Acme Electric Warranty Card  
[www.hubbell-acmeElectric.com/Images/news/Acme\\_Warranty.pdf](http://www.hubbell-acmeElectric.com/Images/news/Acme_Warranty.pdf)