

Technical data sheet · LUTZE Single Conductor Hook Up Wire with UL/CE/MTW and HAR Approvals



Flexible Single Conductor Hook Up Wire · Multi-Norm

Identification	Type	EA HAR-UL 1×4 SW
	Part-No.	A61201

Use/Application/Characteristics

Application	• Multi rated single-conductor cable for wiring of cabinets and use in electrical and electronic equipment • Specially suited for machines exported to Europe (HAR) and North America (UL MTW + CSA TEW) • MTW rating as required per NFPA 79 for machine tool wiring
Characteristics	• Fine stranding class 5, per VDE 0295 • Very flexible for easy installation • Free from silicone and other varnish damaging substances • Conditionally resistant to oils, solvents, acids and bases • MTW rated • RoHS compliant

Construction

Description	SINGLE CONDUCTOR HOOK UP WIRE MULTI-NORM
Number of conductors/cross-section	1×4
Cross-section AWG	AWG 12
Cross-section, metric	4 mm ²
Jacket color	black RAL 9005
Outer Ø	4.3 mm
Outer Ø	0.169 inch

25.01.2020 – Subject to technical modification

Part-No. A61201

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

Technical data sheet · LUTZE Single Conductor Hook Up Wire with UL/CE/MTW and HAR Approvals

Weight	4.6 kg/100 m
Weight	31 Lbs/Mft
Cu-Index	3.7 kg/100 m
Cu-Index	25 Lbs/Mft

Element 1

Element construction	AWG12/1C
Conductor	CU-wire tin-plated
Conductor category	Finely stranded DIN VDE 0295 IEC 60228, Class 5
Conductor marking	black
Conductor insulation	PVC
Conductor insulation standard	UL 1581 Class 43 heat and humidity resistant

Technical data

Rated voltage U_0/U	450/750 V
Rated voltage UL	600 V
Test voltage type	AC 3000 V
Temperature range moving	-5 °C ... +105 °C
Temperature range fixed	-40 °C ... +105 °C
Minimum bending radius fixed	5×D

Element 1

Element construction	AWG12/1C
----------------------	----------

Certifications/Standards

Certifications	cULus cURus UL 1063 MTW Listed TEW HAR HAR: HD 21.3 S3
UL style	AWM 1015
Conformity	CE RoHS REACH
Burning behavior according to	UL VW-1 IEC 60332-1

General

Note	CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU
------	--

25.01.2020 – Subject to technical modification

Part-No. A61201

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

Technical data sheet · LUTZE Single Conductor Hook Up Wire with UL/CE/MTW and HAR Approvals

Symbols



25.01.2020 – Subject to technical modification

Part-No. A61201

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk