



TUV T5

TUV 36T5 HO 4P SE 32PK

TUV T5 lamps are single- or double-ended UVC (germicidal) lamps used in professional water and air disinfection units. The small 16 mm diameter of the lamp allows for a small system design and design flexibility. TUV T5 lamps offer constant UV output over their complete lifetime, for maximum security of disinfection and high system efficacy.

Product data

General Information	
Cap-Base	4PINSSINGLEENDED [4 Pins Single Ended]
Main Application	Disinfection
Useful Life (Nom)	9000 h
System Description	High Output (HO)
Light Technical	
Color Code	- [Not Specified]
Color Designation	- [Not Specified]
Depreciation at Useful Lifetime	15 %
Operating and Electrical	
Power (Rated) (Nom)	75 W
Lamp Current (Nom)	0.8 A
Voltage (Nom)	97 V


Mechanical and Housing	
Cap-Base Information	4 Pins Single Ended
UV	
UV-C Radiation	25 W
Product Data	
Order product name	TUV 36T5 HO 4P SE UNP/32
EAN/UPC - Product	8711500869708
Order code	133892
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	32
Material Nr. (12NC)	927972104099
Net Weight (Piece)	87.000 g

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- DANGER: Risk Group 3 Ultra Violet product. These lamps emit high-power UV radiation that can cause severe injury to skin and eyes. Avoid eye and skin exposure to unshielded product. Use only in an enclosed environment which shields users from the radiation.
- Lamp contains mercury. Manage in Accord with Disposal Laws. See: www.lamprecycle.org or 1-800-555-0050

TUV T5



Dimensional drawing



Product	D (max)	C (max)	A (max)
TUV 36T5 HO 4P SE UNP/32	19.3 mm	853 mm	845.4 mm

TUV 36T5 HO 4P SE

Photometric data



TUV

TUV

