



Price\* : 489.90 USD



### Main

Product or component type	Manual Starter
Range of product	M
Product certifications	UL listed CSA
Auxiliary contact composition	Without
NEMA degree of protection	NEMA 12 painted sheet steel
Local signalling	No indicator
Motor power hp	10 hp 380...575 V AC 3 phases 7.5 hp 200...230 V AC 3 phases
[Ue] rated operational voltage	600 V AC
NEMA size	M-1
Poles description	3P
Control type	Push-button
Motor starter type	Non reversing
Electrical connection	Pressure wire clamp
Thermal overload type	Melting alloy
Number of thermal units required	3

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

### Ordering and shipping details

Category	21103 - 2510,2511,2512 M,T
Discount Schedule	CP1
GTIN	00785901845317
Nbr. of units in pkg.	1
Package weight(Lbs)	7.1200000000000001
Returnability	Y
Country of origin	MX

## Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will not be compliant Will not be compliant
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

## Contractual warranty

Warranty period	18 months
-----------------	-----------